

TRAILERMAN

By Novae®

SOLID SIDE UTILITY



SOLID SIDE UTILITY STANDARD FEATURES

12-Gauge Steel Frame
Angle Crossmembers
Channel Tongue
15" Tall, 12-Gauge Steel Sides
Posi-Lock Coupler with Safety Chains
Enclosed Sealed Wiring Harness
Top Wind Coupler Mount Jack with Foot

50" Spring Assisted Gate and Grab Handle
Steel Radius Fenders
Leaf Spring Suspension
Easy Lube Hubs
Radial Tires on White Steel Wheels
Powder Coat Finish

2" Treated Lumber Decking
Welded Front Board Retainer and Rear End Cap
Side Mounted D-Rings
Spare Tire Carrier
Lockable, Tongue Mounted A-Frame Toolbox
Full LED, DOT Compliant Lighting

SPECIFICATIONS

	60" x 8' SA	60" x 10' SA	76" x 10' SA	76" x 12' SA	82" x 12' SA	82" x 14' SA
Model	HT6008SUT-030	HT6010SUT-030	HT7610SUT-030	HT7612SUT-030	HT8212SUT-030	HT8214SUT-030
GAWR (lbs/axle)	3500	3500	3500	3500	3500	3500
GVWR (lbs)	2990	2900	2990	2990	2990	2990
Curb Weight (lbs)	970	1080	1280	1400	1545	1640
Load Capacity (lbs)	2020	1820	1710	1590	1445	1350
Main Frame	12-Gauge Steel					
Crossmembers	3" x 2" x 3/16" Steel Angle					
Top Rail	N/A					
Uprights	12-Gauge Steel Sides					
Tongue	3" Steel Channel					
Coupler	2" A-Frame					
Jack	2K Rated, Top Wind Coupler Mount					
Axle	(1) 3500 lb Idler Easy Lube Hubs					
Suspension	Leaf Spring					
Tires	ST205-75R-15" 6-PR					
Wheels	15", 5-Hole					
Lights	LED					
Electric Plug	4-Prong Flat					
Decking	2" Treated Lumber					
Finish	Power Coat High Gloss Black					
Gate Style	Spring Assist Gate					
Gate Height	50"	50"	50"	50"	50"	50"
Gate Width	56"	56"	72"	72"	78"	78"
Gate Load Capacity (lbs)	2500	2500	2500	2500	2500	2500
Overall Length	12'-2"	14'-2"	14'-2"	16'-2"	16'-2"	18'-2"
Overall Width	80 1/2"	80 1/2"	94 1/2"	94 1/2"	102"	102"
Deck Length	8'-2"	10'-2"	10'-2"	12'-2"	12'-2"	14'-2"
Deck Width (Between Fenders)	60 1/4"	60 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

